

HIGH DENSITY LEDs

With both 45W and 80W LED variants available, light output is maximised through use of the latest, most advanced and efficient LED technology available.



OVER VOLTAGE PROTECTION

In-built into the electronic circuitry to prevent damage, alongside protection against reverse polarity.

5,000 KELVIN COLOUR TEMPERATURE FOR MAXIMUM DEFINITION

While reducing fatigue and eye strain that can come from using higher colour ranges.

MALE & FEMALE DEUTSCH CONNECTORS INCLUDED

Part no. DT06-2S / DT04-2P.

LAZER

HIGH PERFORMANCE LIGHTING

UTILITY SERIES

HEAVY DUTY LED WORK LAMP



EMC PROTECTION

Approved to CISPR-25 Class 3 ensures no interference with other electrical machinery or appliances.

VACUUM-METALLISED REFLECTOR TECHNOLOGY

Designed and engineered in the UK to deliver light further and wider, in a symmetrical flood beam pattern.



UTILITY-45
45W
4560 LUMENS

UTILITY-80
80W
8820 LUMENS

CAE OPTIMISED 'MATRIX' COOLING SYSTEM

Provides more efficient thermal management to maximise light output.

WIDE MOUNTING OPTION & SLIMLINE MOUNTING OPTION

Both provide 360° rotation, and 120° angle up / down, from a horizontal or vertical mounting position.

AUTOMOTIVE GRADE CORROSION RESISTANCE

E-coat pre-treatment prior to black powder coating ensures exceptional corrosion resistance including against harsh chemical treatments.

ELECTRONIC THERMAL MANAGEMENT

Optimises light output considering the environmental and thermal conditions of the lamp.

'UNBREAKABLE' POLYCARBONATE LENS

3mm lexan polycarbonate with hardcoat lacquer provides exceptional protection from impact and heat.

